

EPOXY-COATED WIRE SHELVES

◆ Withstands temperatures from -100°F to 500°F

Must buy full case quantity

· ividoi	bay ian baco qua	,	
ITEM	DESCRIPTION - W x L	UOM	CASE
VEX-1424	14" x 24"	Each	2
VEX-1430	14" x 30"	Each	2
VEX-1436	14" x 36"	Each	2
VEX-1448	14" x 48"	Each	2
VEX-1460	14" x 60"	Each	2
VEX-1472	14" x 72"	Each	2
VEX-1824	18" x 24"	Each	2
VEX-1830	18" x 30"	Each	2
VEX-1836	18" x 36"	Each	2
VEX-1842	18" x 42"	Each	2
VEX-1848	18" x 48"	Each	2
VEX-1854	18" x 54"	Each	2
VEX-1860	18" x 60"	Each	2
VEX-1872	18" x 72"	Each	2
VEX-2124	21" x 24"	Each	2
VEX-2130	21" x 30"	Each	2
VEX-2136	21" x 36"	Each	2
VEX-2148	21" x 48"	Each	2
VEX-2160	21" x 60"	Each	2
VEX-2172	21" x 72"	Each	2
VEX-2424	24" x 24"	Each	2
VEX-2430	24" x 30"	Each	2
VEX-2436	24" x 36"	Each	2
VEX-2442	24" x 42"	Each	2
VEX-2448	24" x 48"	Each	2
VEX-2454	24" x 54"	Each	2
VEX-2460	24" x 60"	Each	2
VEX-2472	24" x 72"	Each	2

Epoxy shelving suitable for storage in dry as well as moist/humid areas

WIRE SHELVES

- NSF listed for use in all environments, including humid areas
- Heavy-duty wire construction
- Mix-and-match the various sizes to suit any need
- Easy to assemble, no tools required
- Capacities: Under 48" long - up to 850 lbs/shelf, Over 48" long - up to 600 lbs/shelf
- Includes 4 split-sleeve clips per shelf





VEX-SERIES SHELVES NSE





EPOXY-COATED POSTS

- For wire shelving
- Withstands temperatures from -100°F to 500°F

Must buy full case quantity

ITEM	DESCRIPTION	UOM	CASE
VEX-8P	8"H	Each	4
VEX-34P	34"H	Each	4
VEX-48P	48"H	Each	4
VEX-54P	54"H	Each	4
VEX-63P	63"H	Each	4
VEX-72P	72"H	Each	4
VEX-86P	86"H	Each	4



EPOXY-COATED WALL MOUNT BRACKETS

 A great option for mounting a single wire shelf to the wall with two brackets

Must buy full case quantity

ITEM	DESCRIPTION	UOM	CASE
VEXB-14	14"W	Pair	2
VEXB-18	18"W	Pair	2
VEXB-21	21"W	Pair	2
VEXB-24	24"W	Pair	2



S/N-STYLE HOOK FOR EPOXY-COATED SHELVING

 Holds shelving units together when standing next to or behind each other

ITEM	DESCRIPTION	UOM	CASE
VEX-HK	S/N Hook for VEX-series Shelves	Each	20/200





